



“Save Your Environment  
Recycle Your Waste.”

# Complete range of static and portable compactors



*Standard  
and bespoke systems  
to suit all applications*



# KK Static and Portable Compactor

The KK range of compactors are designed to deal efficiently with all types of general waste. Units are installed by our qualified engineers with full certified training given to operatives following installation.

## TECHNICAL DATA

Parameter / Model		10-10	12-10S	12-10	14-15	16-15	18-20	20-20
Motor Rating	kW	7	7	7	11	11	15	15
Power Supply	Volt	415,3 phase						
Power Supply Rating	Amp	32	32	32	45	45	60	60
Control Panel Voltage	Volt	12	12	12	12	12	12	12
Clear Aperture width	mm	1430	1430	1430	1430	1430	1430	1430
Clear Aperture length	mm	1000	1200	1200	1400	1600	1800	2000
Charge Box depth	mm	940	940	940	940	940	940	940
Charge Box volume	m <sup>3</sup>	1.34	1.61	1.61	1.88	2.15	2.05	2.29
CHEM Vol per Hour	m <sup>3</sup>	107	110	110	151	173	164	182
Cycle Time (no load)	sec	38	45	45	45	50	50	50
CHEM Vol per Stroke	m <sup>3</sup>	1.14	1.37	1.37	1.60	1.83	2.05	2.29
Overall Ht (top flange)	mm	1300	1300	1300	1300	1300	1300	1300
Overall Ht door Hopper	mm	2450	2450	2450	2450	2450	2450	2450
Overall length	mm	3100	2000	3620	3963	4578	5380	5690
Overall width	mm	1720	1720	1720	1720	1720	1720	1720
Basic Hydr Pressure	bar	150	150	150	150	150	150	150
Hydraulic Capacity	l.	90	90	90	90	90	120	120
Total Weight	t.	2.43	2.20	2.33	3.40	3.55	4.30	4.50

## FREE SITE SURVEY AVAILABLE

### OPTIONS:

- Trunion Lifter
- Rear Trunion Lifter
  - Comb Lifter
  - Dock Loader
- Galvanised Safety Cage
- Pre-Crush Compactor
- External and through the wall chutes with interlock doors



**KK BALERS Ltd.**  
www.kkgroupint.com

Victory House, Victory Park Road,  
Addlestone, Weybridge,  
Surrey KT15 2AX, England.  
Tel: +44 (0)1932 852423  
Fax: +44 (0)1932 847170

email: [sales@kkbalers.com](mailto:sales@kkbalers.com)

CE Compliant

DEALER STAMP

We reserve the right of design modifications